Pharmacy Plus Bluetooth

Enabled Refrigerator

47L Pharmacy Plus Upright Fridge with Glass Door

GDMAcode PPGR47BT-UK

SKU code 444411306









Key features

- ✓ Local monitoring and alarm history via Bluetooth
- ✓ Power failure alarm with backup battery powered recording
- √ Solid and glass door options
- ✓ Intelligent fan management system for enhanced performance











Bluetooth Connected Controller

Local temperature monitoring and alarm history via Bluetooth connectivity. Power failure alarm with battery back-up, providing continuous temperature monitoring in the event of power outage.

Lec Medical Smartphone App

Contactless local monitoring of air and load temperatures via smart phone app. Downloadable temperature report and alarm history.

Intelligent Fan Management

Smart fan optimisation aides in temperature stability following door openings, minimising fan activity when door is open to reduce the rate of temperature increase.

Dual Probe Temperature Monitoring

Our dual probe system offers greater temperature accuracy within your appliance, simultaneously measuring both air and product temperatures.

Flexible Internal Storage

Multiple shelf locations provides flexible storage solutions.



Gross Capacity (litres)	47L
Net Capacity (litres)	30L
Unit External Width (mm)	475mm
Unit External Depth (mm)	445mm
Unit External Height (mm) Product Weight (kg)	565mm
Packed Width (mm)	17.5Kg 490mm
Packed Depth (mm)	530mm
Packed Height (mm)	620mm
Packed Weight (kg)	21.5Kg
Country of Origin	UK
Internal Dimensions (mm) (WxDxH)	403mm x 354mm x 425mm
Temperature Range	+2°C to +8°C
Colour	White/Green
External Finish	Painted Steel
Internal Finish	HIPS*
Type of plastic	SRL800 (HIPS/ABS mix)
Door Finish	PVC/Glass
Door Type	Glass
Door Style Door Liner	Hinged, Reversible
Number of Door Trays	Flat n/a
Number of Door Tray Positions	n/a
Door Open Depth (mm)	905mm
Replacement Door Seal	No
Open Door Sensor	Yes
Lock	Yes, 2 Keys
Adjustable Feet (number & position)	2 adjustable (front)
Porthole	Yes
Porthole Size	16mm
Porthole Location	Rear LH Corner
Temperature Display on Panel	Yes
Temperature Alarm	Yes
Remote Alarm Contacts	Yes
Audible Alarms	Yes
Visual Alarms Number of Shelves/Drawers	Yes 1
Number of Shelf Positions	3
Shelf Size (mm) (WxDxH)	416mm x 200mm x 6mm
Shelf Size (mm) (WxDxH) Shelf Material	416mm x 200mm x 6mm Polythene Coated Wire
Shelf Size (mm) (WxDxH) Shelf Material Drawer Size (mm) (WxDxH)	416mm x 200mm x 6mm Polythene Coated Wire n/a
Shelf Size (mm) (WxDxH) Shelf Material Drawer Size (mm) (WxDxH) Drawer Material Number of Baskets Basket Material	416mm x 200mm x 6mm Polythene Coated Wire n/a n/a 1 Polythene Coated Wire
Shelf Size (mm) (WxDxH) Shelf Material Drawer Size (mm) (WxDxH) Drawer Material Number of Baskets Basket Material Basket Size (mm) (WxDxH)	416mm x 200mm x 6mm Polythene Coated Wire n/a n/a 1 Polythene Coated Wire 396mm x 165mm x 150mm
Shelf Size (mm) (WxDxH) Shelf Material Drawer Size (mm) (WxDxH) Drawer Material Number of Baskets Basket Material Basket Size (mm) (WxDxH) Interior Light	416mm x 200mm x 6mm Polythene Coated Wire n/a n/a 1 Polythene Coated Wire 396mm x 165mm x 150mm Yes
Shelf Size (mm) (WxDxH) Shelf Material Drawer Size (mm) (WxDxH) Drawer Material Number of Baskets Basket Material Basket Size (mm) (WxDxH) Interior Light Light Type	416mm x 200mm x 6mm Polythene Coated Wire n/a n/a 1 Polythene Coated Wire 396mm x 165mm x 150mm Yes LED
Shelf Size (mm) (WxDxH) Shelf Material Drawer Size (mm) (WxDxH) Drawer Material Number of Baskets Basket Material Basket Size (mm) (WxDxH) Interior Light Light Type Light Activation	416mm x 200mm x 6mm Polythene Coated Wire n/a n/a 1 Polythene Coated Wire 396mm x 165mm x 150mm Yes LED Door Switch / Controller
Shelf Size (mm) (WxDxH) Shelf Material Drawer Size (mm) (WxDxH) Drawer Material Number of Baskets Basket Material Basket Size (mm) (WxDxH) Interior Light Light Type Light Activation Fan	416mm x 200mm x 6mm Polythene Coated Wire n/a n/a 1 Polythene Coated Wire 396mm x 165mm x 150mm Yes LED Door Switch / Controller Yes - Axial
Shelf Size (mm) (WxDxH) Shelf Material Drawer Size (mm) (WxDxH) Drawer Material Number of Baskets Basket Material Basket Size (mm) (WxDxH) Interior Light Light Type Light Activation Fan Spark Free	416mm x 200mm x 6mm Polythene Coated Wire n/a n/a 1 Polythene Coated Wire 396mm x 165mm x 150mm Yes LED Door Switch / Controller Yes - Axial No
Shelf Size (mm) (WxDxH) Shelf Material Drawer Size (mm) (WxDxH) Drawer Material Number of Baskets Basket Material Basket Size (mm) (WxDxH) Interior Light Light Type Light Activation Fan Spark Free Defrost setting	416mm x 200mm x 6mm Polythene Coated Wire n/a n/a 1 Polythene Coated Wire 396mm x 165mm x 150mm Yes LED Door Switch / Controller Yes - Axial No Auto (Off Cycle)
Shelf Size (mm) (WxDxH) Shelf Material Drawer Size (mm) (WxDxH) Drawer Material Number of Baskets Basket Material Basket Size (mm) (WxDxH) Interior Light Light Type Light Activation Fan Spark Free Defrost setting Controller Type	416mm x 200mm x 6mm Polythene Coated Wire n/a n/a 1 Polythene Coated Wire 396mm x 165mm x 150mm Yes LED Door Switch / Controller Yes - Axial No Auto (Off Cycle) Digital BT, External
Shelf Size (mm) (WxDxH) Shelf Material Drawer Size (mm) (WxDxH) Drawer Material Number of Baskets Basket Material Basket Size (mm) (WxDxH) Interior Light Light Type Light Activation Fan Spark Free Defrost setting	416mm x 200mm x 6mm Polythene Coated Wire n/a n/a 1 Polythene Coated Wire 396mm x 165mm x 150mm Yes LED Door Switch / Controller Yes - Axial No Auto (Off Cycle)
Shelf Size (mm) (WxDxH) Shelf Material Drawer Size (mm) (WxDxH) Drawer Material Number of Baskets Basket Material Basket Size (mm) (WxDxH) Interior Light Light Type Light Activation Fan Spark Free Defrost setting Controller Type Battery Back Up/Hours	416mm x 200mm x 6mm Polythene Coated Wire n/a n/a 1 Polythene Coated Wire 396mm x 165mm x 150mm Yes LED Door Switch / Controller Yes - Axial No Auto (Off Cycle) Digital BT, External No
Shelf Size (mm) (WxDxH) Shelf Material Drawer Size (mm) (WxDxH) Drawer Material Number of Baskets Basket Material Basket Size (mm) (WxDxH) Interior Light Light Type Light Activation Fan Spark Free Defrost setting Controller Type Battery Back Up/Hours Bluetooth	416mm x 200mm x 6mm Polythene Coated Wire n/a n/a 1 Polythene Coated Wire 396mm x 165mm x 150mm Yes LED Door Switch / Controller Yes - Axial No Auto (Off Cycle) Digital BT, External No Yes
Shelf Size (mm) (WxDxH) Shelf Material Drawer Size (mm) (WxDxH) Drawer Material Number of Baskets Basket Material Basket Size (mm) (WxDxH) Interior Light Light Type Light Activation Fan Spark Free Defrost setting Controller Type Battery Back Up/Hours Bluetooth NFC	416mm x 200mm x 6mm Polythene Coated Wire n/a n/a 1 Polythene Coated Wire 396mm x 165mm x 150mm Yes LED Door Switch / Controller Yes - Axial No Auto (Off Cycle) Digital BT, External No Yes Yes Yes Yes
Shelf Size (mm) (WxDxH) Shelf Material Drawer Size (mm) (WxDxH) Drawer Material Number of Baskets Basket Material Basket Size (mm) (WxDxH) Interior Light Light Type Light Activation Fan Spark Free Defrost setting Controller Type Battery Back Up/Hours Bluetooth NFC WIFI	416mm x 200mm x 6mm Polythene Coated Wire n/a n/a 1 Polythene Coated Wire 396mm x 165mm x 150mm Yes LED Door Switch / Controller Yes - Axial No Auto (Off Cycle) Digital BT, External No Yes Yes Yes No Air & Load (Glycol Solution)
Shelf Size (mm) (WxDxH) Shelf Material Drawer Size (mm) (WxDxH) Drawer Material Number of Baskets Basket Material Basket Size (mm) (WxDxH) Interior Light Light Type Light Activation Fan Spark Free Defrost setting Controller Type Battery Back Up/Hours Bluetooth NFC WIFI Number of Probes Probe Type Ambient Temperature Range	416mm x 200mm x 6mm Polythene Coated Wire n/a n/a 1 Polythene Coated Wire 396mm x 165mm x 150mm Yes LED Door Switch / Controller Yes - Axial No Auto (Off Cycle) Digital BT, External No Yes Yes Yes No 2 Air & Load (Glycol Solution) 10°C to 32°C
Shelf Size (mm) (WxDxH) Shelf Material Drawer Size (mm) (WxDxH) Drawer Material Number of Baskets Basket Material Basket Size (mm) (WxDxH) Interior Light Light Type Light Activation Fan Spark Free Defrost setting Controller Type Battery Back Up/Hours Bluetooth NFC WIFI Number of Probes Probe Type Ambient Temperature Range Refrigerant Type	416mm x 200mm x 6mm Polythene Coated Wire n/a n/a 1 Polythene Coated Wire 396mm x 165mm x 150mm Yes LED Door Switch / Controller Yes - Axial No Auto (Off Cycle) Digital BT, External No Yes Yes Yes Ara Load (Glycol Solution) 10°C to 32°C R600a
Shelf Size (mm) (WxDxH) Shelf Material Drawer Size (mm) (WxDxH) Drawer Material Number of Baskets Basket Material Basket Size (mm) (WxDxH) Interior Light Light Type Light Activation Fan Spark Free Defrost setting Controller Type Battery Back Up/Hours Bluetooth NFC WIFI Number of Probes Probe Type Ambient Temperature Range Refrigerant Type CFC Free	416mm x 200mm x 6mm Polythene Coated Wire n/a n/a 1 Polythene Coated Wire 396mm x 165mm x 150mm Yes LED Door Switch / Controller Yes - Axial No Auto (Off Cycle) Digital BT, External No Yes Yes Yes Yes Yes Are Aire Alta (Glycol Solution) 10°C to 32°C R600a Yes
Shelf Size (mm) (WxDxH) Shelf Material Drawer Size (mm) (WxDxH) Drawer Material Number of Baskets Basket Material Basket Size (mm) (WxDxH) Interior Light Light Type Light Activation Fan Spark Free Defrost setting Controller Type Battery Back Up/Hours Bluetooth NFC WIFI Number of Probes Probe Type Ambient Temperature Range Refrigerant Type CFC Free HFC Free	416mm x 200mm x 6mm Polythene Coated Wire n/a n/a 1 Polythene Coated Wire 396mm x 165mm x 150mm Yes LED Door Switch / Controller Yes - Axial No Auto (Off Cycle) Digital BT, External No Yes Yes Yes Yes Air & Load (Glycol Solution) 10°C to 32°C R600a Yes
Shelf Size (mm) (WxDxH) Shelf Material Drawer Size (mm) (WxDxH) Drawer Material Number of Baskets Basket Material Basket Size (mm) (WxDxH) Interior Light Light Type Light Activation Fan Spark Free Defrost setting Controller Type Battery Back Up/Hours Bluetooth NFC WIFI Number of Probes Probe Type Ambient Temperature Range Refrigerant Type CFC Free HFC Free	416mm x 200mm x 6mm Polythene Coated Wire n/a n/a 1 Polythene Coated Wire 396mm x 165mm x 150mm Yes LED Door Switch / Controller Yes - Axial No Auto (Off Cycle) Digital BT, External No Yes Yes Yes Arial No Yes Yes Yes Yes No 2 Air & Load (Glycol Solution) 10°C to 32°C R600a Yes
Shelf Size (mm) (WxDxH) Shelf Material Drawer Size (mm) (WxDxH) Drawer Material Number of Baskets Basket Material Basket Size (mm) (WxDxH) Interior Light Light Type Light Activation Fan Spark Free Defrost setting Controller Type Battery Back Up/Hours Bluetooth NFC WIFI Number of Probes Probe Type Ambient Temperature Range Refrigerant Type CFC Free HFC Free HHCFC Free Ammonia Free	416mm x 200mm x 6mm Polythene Coated Wire n/a n/a n/a 1 Polythene Coated Wire 396mm x 165mm x 150mm Yes LED Door Switch / Controller Yes - Axial No Auto (Off Cycle) Digital BT, External No Yes Yes Yes Arial No Yes Yes Yes Yes No 2 Air & Load (Glycol Solution) 10°C to 32°C R600a Yes
Shelf Size (mm) (WxDxH) Shelf Material Drawer Size (mm) (WxDxH) Drawer Material Number of Baskets Basket Material Basket Size (mm) (WxDxH) Interior Light Light Type Light Activation Fan Spark Free Defrost setting Controller Type Battery Back Up/Hours Bluetooth NFC WIFI Number of Probes Probe Type Ambient Temperature Range Refrigerant Type CFC Free HFC Free HHCFC Free Ammonia Free UK 3 Pin Plug	416mm x 200mm x 6mm Polythene Coated Wire n/a n/a 1 Polythene Coated Wire 396mm x 165mm x 150mm Yes LED Door Switch / Controller Yes - Axial No Auto (Off Cycle) Digital BT, External No Yes Yes Yes Yes No 2 Air & Load (Glycol Solution) 10°C to 32°C R600a Yes
Shelf Size (mm) (WxDxH) Shelf Material Drawer Size (mm) (WxDxH) Drawer Material Number of Baskets Basket Material Basket Size (mm) (WxDxH) Interior Light Light Type Light Activation Fan Spark Free Defrost setting Controller Type Battery Back Up/Hours Bluetooth NFC WIFI Number of Probes Probe Type Ambient Temperature Range Refrigerant Type CFC Free HFC Free HFC Free HCFC Free Ammonia Free UK 3 Pin Plug Other Plug Types Available	416mm x 200mm x 6mm Polythene Coated Wire n/a n/a n/a 1 Polythene Coated Wire 396mm x 165mm x 150mm Yes LED Door Switch / Controller Yes - Axial No Auto (Off Cycle) Digital BT, External No Yes Yes Yes Air & Load (Glycol Solution) 10°C to 32°C R600a Yes
Shelf Size (mm) (WxDxH) Shelf Material Drawer Size (mm) (WxDxH) Drawer Material Number of Baskets Basket Material Basket Size (mm) (WxDxH) Interior Light Light Type Light Activation Fan Spark Free Defrost setting Controller Type Battery Back Up/Hours Bluetooth NFC WIFI Number of Probes Probe Type Ambient Temperature Range Refrigerant Type CFC Free HFC Free HFC Free HCFC Free Ammonia Free UK 3 Pin Plug Other Plug Types Available Voltage Supply	416mm x 200mm x 6mm Polythene Coated Wire n/a n/a 1 Polythene Coated Wire 396mm x 165mm x 150mm Yes LED Door Switch / Controller Yes - Axial No Auto (Off Cycle) Digital BT, External No Yes Yes Yes Yes No 2 Air & Load (Glycol Solution) 10°C to 32°C R600a Yes
Shelf Size (mm) (WxDxH) Shelf Material Drawer Size (mm) (WxDxH) Drawer Material Number of Baskets Basket Material Basket Size (mm) (WxDxH) Interior Light Light Type Light Activation Fan Spark Free Defrost setting Controller Type Battery Back Up/Hours Bluetooth NFC WIFI Number of Probes Probe Type Ambient Temperature Range Refrigerant Type CFC Free HFC Free HFC Free HCFC Free Ammonia Free UK 3 Pin Plug Other Plug Types Available	416mm x 200mm x 6mm Polythene Coated Wire n/a n/a 1 Polythene Coated Wire 396mm x 165mm x 150mm Yes LED Door Switch / Controller Yes - Axial No Auto (Off Cycle) Digital BT, External No Yes Yes No 2 Air & Load (Glycol Solution) 10°C to 32°C R600a Yes
Shelf Size (mm) (WxDxH) Shelf Material Drawer Size (mm) (WxDxH) Drawer Material Number of Baskets Basket Material Basket Size (mm) (WxDxH) Interior Light Light Type Light Activation Fan Spark Free Defrost setting Controller Type Battery Back Up/Hours Bluetooth NFC WIFI Number of Probes Probe Type Ambient Temperature Range Refrigerant Type CFC Free HFC Free HFC Free HFCF Free HFCF Free UK 3 Pin Plug Other Plug Types Available Voltage Supply Insulation Thickness (mm)	416mm x 200mm x 6mm Polythene Coated Wire n/a n/a 1 Polythene Coated Wire 396mm x 165mm x 150mm Yes LED Door Switch / Controller Yes - Axial No Auto (Off Cycle) Digital BT, External No Yes Yes Yes Yes Yes No 2 Air & Load (Glycol Solution) 10°C to 32°C R600a Yes
Shelf Size (mm) (WxDxH) Shelf Material Drawer Size (mm) (WxDxH) Drawer Material Number of Baskets Basket Material Basket Size (mm) (WxDxH) Interior Light Light Type Light Activation Fan Spark Free Defrost setting Controller Type Battery Back Up/Hours Bluetooth NFC WIFI Number of Probes Probe Type Ambient Temperature Range Refrigerant Type CFC Free HFC Free HFC Free HCFC Free HCFC Free HCFC Free UK 3 Pin Plug Other Plug Types Available Voltage Supply Insulation Type Insulation Type	416mm x 200mm x 6mm Polythene Coated Wire n/a n/a 1 Polythene Coated Wire 396mm x 165mm x 150mm Yes LED Door Switch / Controller Yes - Axial No Auto (Off Cycle) Digital BT, External No Yes Yes Yes Yes Yes Yes No 2 Air & Load (Glycol Solution) 10°C to 32°C R600a Yes Yes Yes Yes Yes Yes Yes Ye
Shelf Size (mm) (WxDxH) Shelf Material Drawer Size (mm) (WxDxH) Drawer Material Number of Baskets Basket Material Basket Size (mm) (WxDxH) Interior Light Light Type Light Activation Fan Spark Free Defrost setting Controller Type Battery Back Up/Hours Bluetooth NFC WIFI Number of Probes Probe Type Ambient Temperature Range Refrigerant Type CFC Free HFC Free HFC Free HCFC Free Ammonia Free UK 3 Pin Plug Other Sluetion Type Insulation Type Blowing Agent	416mm x 200mm x 6mm Polythene Coated Wire n/a n/a 1 Polythene Coated Wire 396mm x 165mm x 150mm Yes LED Door Switch / Controller Yes - Axial No Auto (Off Cycle) Digital BT, External No Yes Yes Yes Yes Air & Load (Glycol Solution) 10°C to 32°C R600a Yes Yes Yes Yes Yes Yes Yes Yes Yes Ye
Shelf Size (mm) (WxDxH) Shelf Material Drawer Size (mm) (WxDxH) Drawer Material Number of Baskets Basket Material Basket Size (mm) (WxDxH) Interior Light Light Type Light Activation Fan Spark Free Defrost setting Controller Type Battery Back Up/Hours Bluetooth NFC WIFI Number of Probes Probe Type Ambient Temperature Range Refrigerant Type CFC Free HFC Free HHCFC Free HHCFC Free Ammonia Free UK 3 Pin Plug Other Plug Types Available Voltage Supply Insulation Type Blowing Agent Anti Microbial Handle	416mm x 200mm x 6mm Polythene Coated Wire n/a n/a 1 Polythene Coated Wire 396mm x 165mm x 150mm Yes LED Door Switch / Controller Yes - Axial No Auto (Off Cycle) Digital BT, External No Yes Yes Yes Air & Load (Glycol Solution) 10°C to 32°C R600a Yes Yes Yes Yes Yes Yes Yes Ye
Shelf Size (mm) (WxDxH) Shelf Material Drawer Size (mm) (WxDxH) Drawer Material Number of Baskets Basket Material Basket Size (mm) (WxDxH) Interior Light Light Type Light Activation Fan Spark Free Defrost setting Controller Type Battery Back Up/Hours Bluetooth NFC WIFI Number of Probes Probe Type Ambient Temperature Range Refrigerant Type CFC Free HFC Free HCFC Free Ammonia Free UK 3 Pin Plug Other Plug Types Available Voltage Supply Insulation Type Blowing Agent Anti Microbial Handle Wall Brackets	416mm x 200mm x 6mm Polythene Coated Wire n/a n/a 1 Polythene Coated Wire 396mm x 165mm x 150mm Yes LED Door Switch / Controller Yes - Axial No Auto (Off Cycle) Digital BT, External No Yes Yes Yes No 2 Air & Load (Glycol Solution) 10°C to 32°C R600a Yes Yes Yes Yes Yes Yes Yes Ye
Shelf Size (mm) (WxDxH) Shelf Material Drawer Size (mm) (WxDxH) Drawer Material Number of Baskets Basket Material Basket Size (mm) (WxDxH) Interior Light Light Type Light Activation Fan Spark Free Defrost setting Controller Type Battery Back Up/Hours Bluetooth NFC WIFI Number of Probes Probe Type Ambient Temperature Range Refrigerant Type CFC Free HFC Free HFC Free HFC Free HFC Free Ammonia Free UK 3 Pin Plug Other Plug Types Available Voltage Supply Insulation Thickness (mm) Insulation Type Blowing Agent Anti Microbial Handle Wall Brackets Optional Drawer System	416mm x 200mm x 6mm Polythene Coated Wire n/a n/a 1 Polythene Coated Wire 396mm x 165mm x 150mm Yes LED Door Switch / Controller Yes - Axial No Auto (Off Cycle) Digital BT, External No Yes Yes No 2 Air & Load (Glycol Solution) 10°C to 32°C R600a Yes

